

# Armaflex® MC

THE FLEXIBLE INSULATION WITH A  
BUILT-IN VAPOR BARRIER



- Excellent, built-in condensation control due to closed-cell structure
- Low thermal conductivity  $\lambda_0 \text{ °C} \leq 0.034 \text{ W/(m · K)}$
- High water vapor resistance  $\mu \geq 7,000$
- GREENGUARD® certified for low chemical emissions
- Flexible and fibre-free for easy installation



## Technical Data - Armaflex® MC

Brief description	Flexible closed-cell material with microcell technology offers reliable condensation control and excellent thermal conductivity.												
Material type	Elastomeric foam based on nitrile rubber												
Colour	Black												
Applications	Insulation / protection for pipes and ducts of air-conditioning, refrigeration and chilled water systems to prevent condensation and save energy.												
Assembly	The Armaflex® installation manual should be consulted before installation. We offer special installation training for the application of Armaflex®. For outdoor application, Arma-Chek® cladding should be used. Please contact our Technical Department.												
Property	Value/Assessment							Test* <sup>1</sup>					
Temperature Range								Special Remark					
Temperature Range	max. service temperature	+ 105 °C			( + 85 °C if sheet or tape is glued to the object with its whole surface)			For applications between - 50 °C and - 200 °C, please contact our Technical Department.					
	min. service temperature	- 50 °C											
Thermal Conductivity													
Thermal Conductivity	$\vartheta_m$	-20 [-4]	+/-0 [32]	24 [75]	32 [90]	40 [104]	°C [°F]	ASTM C 177					
	$\lambda$	≤ 0.032	0.034	0.036	0.037	0.039	W/(m · K)						
		≤ 0.230	0.240	0.250	0.260	0.270	Btu·in/(h·ft²·°F)						
Water vapour diffusion resistance													
Water vapour diffusion resistance	< 2.8 x 10 <sup>-11</sup> g/(m·s·Pa)							DIN EN 13469					
	Water Vapor Permeability	$\mu$	≥			7,000		DIN EN 12086					
Fire performance													
Reaction to fire	Flammability							UL94					
Other Fire Class													
Practical Fire Behaviour	Self-extinguishing, no fire dripping												
Acoustic Performance													
Reduction of structure-borne sound transmission	Sound Absorption Co-efficient: Up to 0.55 at 1,000 Hz							ISO 354:2003					
Other technical features								Also suitable for use in the prevention of sound passage					
UV resistance	For UV protection, Armafinish Paint 99 or Arma-Chek® Silver 350 is required.												
Health aspects	Dust- and fibre-free Free of formaldehyde Low VOC, Low Total Aldehyde							GREENGUARD® Gold for even lower VOC and total chemical emissions					
Water Absorption	$\leq 0.05\%$ by volume							ASTM C 209					
Corrosion on Copper or Steel Pipe	No corrosion							DIN 1988 Part 7					
Environmental Aspect	Zero ODP and zero GWP												

\*1 Further documents such as test certificates, approvals and the like can be requested using the registration number given.

All data and technical information are based on results achieved under typical application conditions. Recipients of this information should, in their own interest and responsibility, clarify with us in due time whether or not the data and information apply to the intended application area. For outside use, Armaflex should be protected with Armafinish Paint or Arma-Chek covering within 3 days of installation.

# Armaflex® MC tubes



Length 2.0 m, Color black

Pipe max. Outside-Ø [mm]	Inner Ø min/ max mm	6.0 mm (1/4 inch) insulation thickness				9.0 mm (3/8 inch) insulation thickness			
		Cu Pipe OD [inch]	Code	Tubes/carton	m/carton	Cu Pipe OD [inch]	Code	Tubes/carton	m/carton
6	6.5 - 8.5	-	-	-	-	1/4"	<b>MC-F-006</b>	176	352
10	9.5 - 11.5	-	-	-	-	3/8"	<b>MC-F-010</b>	132	264
12	13.0 - 15.0	-	-	-	-	1/2"	<b>MC-F-012</b>	120	240
15	16.0 - 18.0	5/8"	<b>MC-D-015</b>	143	286	5/8"	<b>MC-F-015</b>	100	200
20	19.5 - 21.5	3/4"	<b>MC-D-020</b>	110	220	3/4"	<b>MC-F-020</b>	72	144
22	22.5 - 24.5	7/8"	<b>MC-D-022</b>	100	200	7/8"	<b>MC-F-022</b>	68	136
25	27.0 - 29.0	1"	<b>MC-D-025</b>	81	162	1"	<b>MC-F-025</b>	63	126
28	29.0 - 31.0	1-1/8"	<b>MC-D-028</b>	68	136	1-1/8"	<b>MC-F-028</b>	49	98
32	31.5 - 34.0	-	-	-	-	1-1/4"	<b>MC-F-032</b>	42	84
35	35.0 - 37.5	1-3/8"	<b>MC-D-035</b>	53	106	1-3/8"	<b>MC-F-035</b>	42	84
42	42.5 - 45.0	-	-	-	-	1-5/8"	<b>MC-F-042</b>	35	70
48	48.5 - 51.0	-	-	-	-	1-7/8"	<b>MC-F-048</b>	28	56
54	54.5 - 57.0	-	-	-	-	2-1/8"	<b>MC-F-054</b>	24	48
60	60.5 - 63.0	-	-	-	-	2-3/8"	<b>MC-F-060</b>	24	48

Pipe max. Outside-Ø [mm]	Inner Ø min/ max mm	13.0 mm (1/2 inch) insulation thickness				19.0 mm (3/4 inch) insulation thickness			
		Cu Pipe OD [inch]	Code	Tubes/carton	m/carton	Cu Pipe OD [inch]	Code	Tubes/carton	m/carton
6	6.5 - 8.5	1/4"	<b>MC-H-006</b>	90	180	1/4"	<b>MC-M-006</b>	56	112
10	9.5 - 11.5	3/8"	<b>MC-H-010</b>	90	180	3/8"	<b>MC-M-010</b>	46	92
12	13.0 - 15.0	1/2"	<b>MC-H-012</b>	72	144	1/2"	<b>MC-M-012</b>	39	78
15	16.0 - 18.0	5/8"	<b>MC-H-015</b>	64	128	5/8"	<b>MC-M-015</b>	39	78
20	19.5 - 21.5	3/4"	<b>MC-H-020</b>	56	112	3/4"	<b>MC-M-020</b>	30	60
22	22.5 - 24.5	7/8"	<b>MC-H-022</b>	53	106	7/8"	<b>MC-M-022</b>	30	60
25	27.0 - 29.0	1"	<b>MC-H-025</b>	42	84	1"	<b>MC-M-025</b>	25	50
28	29.0 - 31.0	1-1/8"	<b>MC-H-028</b>	36	72	1-1/8"	<b>MC-M-028</b>	20	40
32	31.5 - 34.0	1-1/4"	<b>MC-H-032</b>	30	60	1-1/4"	<b>MC-M-032</b>	20	40
35	35.0 - 37.5	1-3/8"	<b>MC-H-035</b>	25	50	1-3/8"	<b>MC-M-035</b>	18	36
38	0.0 - 0.0	-	-	-	-	1-1/2"	<b>MC-M-038</b>	16	32
42	42.5 - 45.0	1-5/8"	<b>MC-H-042</b>	25	50	1-5/8"	<b>MC-M-042</b>	16	32
48	48.5 - 51.0	1-7/8"	<b>MC-H-048</b>	20	40	1-7/8"	<b>MC-M-048</b>	16	32
54	54.5 - 57.0	2-1/8"	<b>MC-H-054</b>	20	40	2-1/8"	<b>MC-M-054</b>	16	32
60	60.5 - 63.0	2-3/8"	<b>MC-H-060</b>	15	30	2-3/8"	<b>MC-M-060</b>	12	24
67	67.5 - 70.5	2-5/8"	<b>MC-H-067</b>	12	24	2-5/8"	<b>MC-M-067</b>	10	20
73	74.0 - 77.0	2-7/8"	<b>MC-H-073</b>	12	24	2-7/8"	<b>MC-M-073</b>	9	18
76	77.0 - 80.0	3"	<b>MC-H-076</b>	12	24	3"	<b>MC-M-076</b>	9	18
80	81.0 - 84.5	3-1/8"	<b>MC-H-080</b>	11	22	3-1/8"	<b>MC-M-080</b>	8	16
89	89.5 - 93.0	3-1/2"	<b>MC-H-089</b>	11	22	3-1/2"	<b>MC-M-089</b>	8	16
105	106.0 - 110.0	4-1/8"	<b>MC-H-105</b>	8	16	4-1/8"	<b>MC-M-105</b>	5	10
114	115.0 - 119.0	4-1/2"	<b>MC-H-114</b>	8	16	4-1/2"	<b>MC-M-114</b>	5	10
140	141.5 - 145.5	-	-	-	-	5-1/2"	<b>MC-M-140</b>	3	6

# Armaflex® MC tubes



Length 2.0 m, Color black

Pipe max. Outside-Ø [mm]	Inner Ø min/ max mm	25.0 mm (1 inch) insulation thickness				32.0 mm (1 1/4 inch) insulation thickness			
		Cu Pipe OD [inch]	Code	Tubes/carton	m/carton	Cu Pipe OD [inch]	Code	Tubes/carton	m/carton
10	9.5 - 11.5	3/8"	<b>MC-R-010</b>	28	56	-	-	-	-
12	13.0 - 15.0	1/2"	<b>MC-R-012</b>	28	56	1/2"	<b>MC-T-012</b>	16	32
15	16.0 - 18.0	5/8"	<b>MC-R-015</b>	20	40	5/8"	<b>MC-T-015</b>	16	32
20	19.5 - 21.5	3/4"	<b>MC-R-020</b>	20	40	3/4"	<b>MC-T-020</b>	12	24
22	22.5 - 24.5	7/8"	<b>MC-R-022</b>	20	40	7/8"	<b>MC-T-022</b>	12	24
25	27.0 - 29.0	1"	<b>MC-R-025</b>	18	36	1"	<b>MC-T-025</b>	12	24
28	29.0 - 31.0	1-1/8"	<b>MC-R-028</b>	16	32	1-1/8"	<b>MC-T-028</b>	12	24
32	31.5 - 34.0	1-1/4"	<b>MC-R-032</b>	14	28	1-1/4"	<b>MC-T-032</b>	12	24
35	35.0 - 37.5	1-3/8"	<b>MC-R-035</b>	14	28	1-3/8"	<b>MC-T-035</b>	9	18
42	42.5 - 45.0	1-5/8"	<b>MC-R-042</b>	11	22	1-5/8"	<b>MC-T-042</b>	8	16
48	48.5 - 51.0	1-7/8"	<b>MC-R-048</b>	11	22	1-7/8"	<b>MC-T-048</b>	6	12
54	54.5 - 57.0	2-1/8"	<b>MC-R-054</b>	9	18	2-1/8"	<b>MC-T-054</b>	6	12
60	60.5 - 63.0	2-3/8"	<b>MC-R-060</b>	9	18	2-3/8"	<b>MC-T-060</b>	6	12
67	67.5 - 70.5	2-5/8"	<b>MC-R-067</b>	8	16	2-5/8"	<b>MC-T-067</b>	5	10
73	74.0 - 77.0	2-7/8"	<b>MC-R-073</b>	8	16	2-7/8"	<b>MC-T-073</b>	4	8
76	77.0 - 80.0	3"	<b>MC-R-076</b>	6	12	3"	<b>MC-T-076</b>	4	8
80	81.0 - 84.5	3-1/8"	<b>MC-R-080</b>	6	12	3-1/8"	<b>MC-T-080</b>	4	8
89	89.5 - 93.0	3-1/2"	<b>MC-R-089</b>	6	12	3-1/2"	<b>MC-T-089</b>	4	8
93	94.0 - 97.5	3-5/8"	<b>MC-R-093</b>	4	8	3-5/8"	<b>MC-T-093</b>	3	6
102	102.0 - 106.0	4"	<b>MC-R-102</b>	4	8	4"	<b>MC-T-102</b>	3	6
105	106.0 - 110.0	4-1/8"	<b>MC-R-105</b>	4	8	4-1/8"	<b>MC-T-105</b>	3	6
114	115.0 - 119.0	4-1/2"	<b>MC-R-114</b>	4	8	4-1/2"	<b>MC-T-114</b>	3	6
140	141.5 - 145.5	5-1/2"	<b>MC-R-140</b>	3	6	5-1/2"	<b>MC-T-140</b>	2	4
168	170.0 - 174.0	6-5/8"	<b>MC-R-168</b>	2	4	6-5/8"	<b>MC-T-168</b>	2	4

Pipe max. Outside-Ø [mm]	Inner Ø min/ max mm	38.0 mm (1 1/2 inch) insulation thickness				50.0 mm (2 inch) insulation thickness			
		Cu Pipe OD [inch]	Code	Tubes/carton	m/carton	Cu Pipe OD [inch]	Code	Tubes/carton	m/carton
15	16.0 - 18.0	5/8"	<b>MC-U-015</b>	11	22	-	-	-	-
20	19.5 - 21.5	3/4"	<b>MC-U-020</b>	11	22	-	-	-	-
22	22.5 - 24.5	7/8"	<b>MC-U-022</b>	11	22	7/8"	<b>MC-V-022</b>	6	12
25	27.0 - 29.0	1"	<b>MC-U-025</b>	8	16	1"	<b>MC-V-025</b>	6	12
28	29.0 - 31.0	1-1/8"	<b>MC-U-028</b>	8	16	1-1/8"	<b>MC-V-028</b>	6	12
32	31.5 - 34.0	1-1/4"	<b>MC-U-032</b>	8	16	1-1/4"	<b>MC-V-032</b>	5	10
35	35.0 - 37.5	1-3/8"	<b>MC-U-035</b>	8	16	1-3/8"	<b>MC-V-035</b>	5	10
42	42.5 - 45.0	1-5/8"	<b>MC-U-042</b>	6	12	1-5/8"	<b>MC-V-042</b>	4	8
48	48.5 - 51.0	1-7/8"	<b>MC-U-048</b>	6	12	1-7/8"	<b>MC-V-048</b>	4	8
54	54.5 - 57.0	2-1/8"	<b>MC-U-054</b>	5	10	2-1/8"	<b>MC-V-054</b>	4	8
60	60.5 - 63.0	2-3/8"	<b>MC-U-060</b>	5	10	2-3/8"	<b>MC-V-060</b>	4	8
67	67.5 - 70.5	2-5/8"	<b>MC-U-067</b>	4	8	2-5/8"	<b>MC-V-067</b>	4	8
73	74.0 - 77.0	2-7/8"	<b>MC-U-073</b>	4	8	2-7/8"	<b>MC-V-073</b>	4	8
76	77.0 - 80.0	3"	<b>MC-U-076</b>	4	8	3"	<b>MC-V-076</b>	3	6
80	81.0 - 84.5	3-1/8"	<b>MC-U-080</b>	4	8	3-1/8"	<b>MC-V-080</b>	3	6
89	89.5 - 93.0	3-1/2"	<b>MC-U-089</b>	4	8	3-1/2"	<b>MC-V-089</b>	3	6
93	94.0 - 97.5	3-5/8"	<b>MC-U-093</b>	3	6	3-5/8"	<b>MC-V-093</b>	3	6
102	102.0 - 106.0	4"	<b>MC-U-102</b>	3	6	4"	<b>MC-V-102</b>	3	6
105	106.0 - 110.0	4-1/8"	<b>MC-U-105</b>	3	6	4-1/8"	<b>MC-V-105</b>	3	6
114	115.0 - 119.0	4-1/2"	<b>MC-U-114</b>	3	6	4-1/2"	<b>MC-V-114</b>	2	4
140	141.5 - 145.5	5-1/2"	<b>MC-U-140</b>	2	4	5-1/2"	<b>MC-V-140</b>	2	4
168	170.0 - 174.0	6-5/8"	<b>MC-U-168</b>	2	4	6-5/8"	<b>MC-V-168</b>	2	4

## Armaflex® MC sheets



Width 1.22 m, Length 0.91 m, Color black

Code	Insulation thickness [mm]	m²/carton
MC-03x122x91	3.0	70
MC-06x122x91	6.0	35
MC-09x122x91	9.0	26
MC-13x122x91	13.0	20
MC-19x122x91	19.0	13
MC-25x122x91	25.0	10
MC-32x122x91	32.0	8
MC-38x122x91	38.0	6
MC-50x122x91	50.0	5

### Remark

The above items are packed in plastic bags.

## Armaflex® MC sheets precut



Width 1.22 m, Color black

Pipe max. Outside-Ø [mm]	13.0 mm (1/2 inch) insulation thickness					19.0 mm (3/4 inch) insulation thickness				
	Code	Width [m]	Length [m]	Pieces/ carton	Fe Pipe Nom. OD [mm]	Code	Width [m]	Length [m]	Pieces/ carton	Fe Pipe Nom. OD [mm]
150	MC-13x122x60	1.22	0.60	20	150	MC-19x122x60	1.22	0.60	13	6
200	MC-13x122x75	1.22	0.75	20	200	MC-19x122x75	1.22	0.75	13	8
250	MC-13x122x95	1.22	0.95	20	250	MC-19x122x95	1.22	0.95	13	10
300	MC-13x122x110	1.22	1.10	20	300	MC-19x122x110	1.22	1.10	13	12
350	MC-13x122x120	1.22	1.20	20	350	MC-19x122x119	1.22	1.25	13	14
400	MC-13x122x135	1.22	1.35	20	400	MC-19x122x140	1.22	1.40	13	16
450	MC-13x122x150	1.22	1.50	20	450	MC-19x122x155	1.22	1.55	13	18
500	MC-13x122x165	1.22	1.65	20	500	MC-19x122x170	1.22	1.70	13	20
550	MC-13x122x185	1.22	1.85	20	550	MC-19x122x185	1.22	1.85	13	22
600	MC-13x122x195	1.22	1.95	20	600	MC-19x122x200	1.22	2.00	13	24

Pipe max. Outside-Ø [mm]	25.0 mm (1 inch) insulation thickness					32.0 mm (1 1/4 inch) insulation thickness				
	Code	Width [m]	Length [m]	Pieces/ carton	Fe Pipe Nom. OD [mm]	Code	Width [m]	Length [m]	Pieces/ carton	Fe Pipe Nom. OD [mm]
150	MC-25x122x60	1.22	0.60	10	6	MC-32x122x67	1.22	0.67	8	6
200	MC-25x122x75	1.22	0.75	10	8	MC-32x122x83	1.22	0.83	8	8
250	MC-25x122x95	1.22	0.95	10	10	MC-32x122x100	1.22	1.00	8	10
300	MC-25x122x110	1.22	1.10	10	12	MC-32x122x116	1.22	1.16	8	12
350	MC-25x122x125	1.22	1.25	10	14	MC-32x122x126	1.22	1.26	8	14
400	MC-25x122x140	1.22	1.40	10	16	MC-32x122x142	1.22	1.42	8	16
450	MC-25x122x155	1.22	1.55	10	18	MC-32x122x158	1.22	1.59	8	18
500	MC-25x122x170	1.22	1.70	10	20	MC-32x122x173	1.22	1.73	8	20
550	MC-25x122x185	1.22	1.85	10	22	MC-32x122x190	1.22	1.90	8	22
600	MC-25x122x200	1.22	2.00	10	24	MC-32x122x210	1.22	2.10	8	24

Pipe max. Outside-Ø [mm]	38.0 mm (1 1/2 inch) insulation thickness					50.0 mm (2 inch) insulation thickness				
	Code	Width [m]	Length [m]	Pieces/ carton	Fe Pipe Nom. OD [mm]	Code	Width [m]	Length [m]	Pieces/ carton	Fe Pipe Nom. OD [mm]
150	MC-38x122x75	1.22	0.75	5	6	MC-50x122x75	1.22	0.75	5	6
200	MC-38x122x95	1.22	0.95	5	8	MC-50x122x95	1.22	0.90	5	8
250	MC-38x122x110	1.22	1.10	5	10	MC-50x122x110	1.22	1.09	5	10
300	MC-38x122x138	1.22	1.25	5	12	MC-50x122x150	1.22	1.25	5	12
350	MC-38x122x140	1.22	1.40	5	14	MC-50x122x140	1.22	1.35	5	14
400	MC-38x122x155	1.22	1.55	5	16	MC-50x122x155	1.22	1.60	5	16
450	MC-38x122x170	1.22	1.70	5	18	MC-50x122x170	1.22	1.70	5	18
500	MC-38x122x185	1.22	1.85	5	20	MC-50x122x185	1.22	1.90	5	20
550	MC-38x122x200	1.22	2.00	5	22	MC-50x122x200	1.22	1.99	5	22
600	MC-38x122x220	1.22	2.20	5	24	MC-50x122x220	1.22	2.15	5	24

### Remark

The above items are packed in plastic bags.

## Armaflex® MC sheets endless



Width 1.0 m and 1.22 m, Color black

1.0 m width				1.22 m width			
Code	Insulation thickness [mm]	Roll length [m]	m <sup>2</sup> /carton	Code	Insulation thickness [mm]	Roll length [m]	m <sup>2</sup> /carton
MC-06100CS-15	6.0	15	15	MC-06122CS-15	6.0	15	18.3
MC-09100CS-10	9.0	10	10	MC-09122CS-10	9.0	10	12.2
MC-13100CS-8	13.0	8	8	MC-13122CS-8	13.0	8	9.76
MC-19100CS-6	19.0	6	6	MC-19122CS-6	19.0	6	7.32
MC-25100CS-4	25.0	4	4	MC-25122CS-4	25.0	4	4.88
MC-32100CS-3	32.0	3	3	MC-32122CS-3	32.0	3	3.66
MC-38100CS-3	38.0	3	3	MC-38122CS-3	38.0	3	3.66
MC-50100CS-3	50.0	3	3	MC-50122CS-3	50.0	3	3.66
-	-	-	-	MC-38122CS-6	38.0	6	7.32
-	-	-	-	MC-50122CS-3	50.0	3	3.66
-	-	-	-	MC-50122CS-6	50.0	6	7.32

**Remark**

The above items are packed in plastic bags.

## Armaflex® MC sheets endless (jumbo rolls)



Width 1.22 m, Length 15 m, Color black

Code	Insulation thickness [mm]	Roll length [m]	m <sup>2</sup> /carton
MC-03x122x1500	3.0	15	18.3
MC-06x122x1500	6.0	15	18.3
MC-09x122x1500	9.0	15	18.3
MC-13x122x1500	13.0	15	18.3
MC-19x122x1500	19.0	15	18.3
MC-25x122x1500	25.0	15	18.3
MC-32x122x600	32.0	6	7.32
MC-38x122x600	38.0	6	7.32
MC-50x122x600	50.0	6	7.32

**Remark**

The above items are packed in plastic bags.

## Armaflex® MC sheets endless self-adhesive



Width 1.0 m and 1.22 m, Color black

1.0 m width				1.22 m width			
Code	Insulation thickness [mm]	Roll length [m]	m <sup>2</sup> /carton	Code	Insulation thickness [mm]	Roll length [m]	m <sup>2</sup> /carton
MC-06100CS-15-T	6.0	15	15	MC-06122CS-15-T	6.0	15	18.3
MC-09100CS-10-T	9.0	10	10	MC-09122CS-10-T	9.0	10	12.2
MC-13100CS-8-T	13.0	8	8	MC-13122CS-8-T	13.0	8	9.76
MC-19100CS-6-T	19.0	6	6	MC-19122CS-6-T	19.0	6	7.32
MC-25100CS-4-T	25.0	4	4	MC-25122CS-4-T	25.0	4	4.88
MC-32100CS-3-T	32.0	3	3	MC-32122CS-6-T	32.0	6	7.32
MC-38100CS-3-T	38.0	3	3	MC-38122CS-6-T	38.0	6	7.32
MC-50100CS-3-T	50.0	3	3	MC-50122CS-6-T	50.0	6	7.32

**Remark**

The above items are packed in plastic bags.

## Armaflex® MC sheets endless self-adhesive (jumbo rolls)



Width 1.22 m, Length 15 m, Color black

Code	Insulation thickness [mm]	Roll length [m]	m <sup>2</sup> /carton
MC-03x122x1500T	3.0	15	18.3
MC-06x122x1500T	6.0	15	18.3
MC-09x122x1500-T	9.0	15	18.3
MC-13x122x1500-T	13.0	15	18.3
MC-19x122x1500-T	19.0	15	18.3
MC-25x122x1500-T	25.0	15	18.3

### Remark

The above items are packed in plastic bags.

## Armaflex® MC tapes self-adhesive



Color black

Code	Article description	Width [mm]	Length [m]	Thickness [mm]	Rolls/carton
MC-03005CS-9.14-T	Armaflex® MC self-adhesive tape, black (9.14m x 50mm x 3mm)	50.0	9.14	3	12
MC-0600025CS-15-T	Armaflex® MC self-adhesive tape, black (15m x 25mm x 6mm)	25.0	15	6	12

## Armaflex® MC accessories



Code	Article description	Pieces/carton
ADH-520-1G	Armaflex® 520 adhesive, 3.78 litre cans	4
ADH520/0,5E	Armaflex® adhesive 520, 0,5 liter cans	12
ADH520/1,0E	Armaflex® adhesive 520, 1,0 liter cans	12
ADH520/3.8-BLV	Armaflex® BLV520 low-VOC adhesive, 3.78 litre cans (LEED certified)	3
ADH820T/0,7-I	Armaflex® 820 adhesive, 0,7 litre cans	12
ADH820T/1G	Armaflex® 820 adhesive, 3.78 litre cans	3
CLEANER/1,0	Special cleaner for use with Armaflex® Adhesive 520 and Armaflex® Adhesive HT625	4
CUTTING-SET	Armaflex® knife-set (3 knives + 1 sharpening stone)	1
GLUEM-BRUSH11MM	Gluemaster extra brush points with cap (11mm diameter)	5x4
GLUEM-BRUSH17MM	Gluemaster extra brush points with cap (17mm diameter)	5x4
GLUEMASTER B	Armaflex® Gluemaster (adhesive pump)	12

**armacell Asia Pte Ltd**  
#12-01 Great World City East Tower, 1 Kim Seng Promenade • 237994 Singapore  
Phone +65 6733 5886 • Fax +65 6733 5887  
[wwwarmacell.com](http://wwwarmacell.com) • [info.singapore@armacell.com](mailto:info.singapore@armacell.com)

[www.armacell.com](http://www.armacell.com) • [info.singapore@armacell.com](mailto:info.singapore@armacell.com)  
**Armacell (Thailand) Limited**  
88 Mu 4, Donkrabueng • 70110 Banpong • Ratchaburi 70110 • Thailand

88 Mu 4, Donkrabueang • 70110 Banpong • Ratchaburi 70110 • Thailand  
Phone +66 (0) 32 353 205-7 • Fax +66 (0) 32 353 208  
[www.armacell.co.th](http://www.armacell.co.th) • [info.thailand@armacell.com](mailto:info.thailand@armacell.com)

**Armacell Asia Ltd. (Vietnam Representative Office)**  
#19-01, 19th Floor, Saigon Trade Centre • 37 Ton Duc Thang Street, District 1 •  
Ho Chi Minh City • Vietnam

Ho Chi Minh City • Vietnam  
Phone +84 8 2220 3832 • Fax +84 8 2220 3833  
[www.armacell.com.vn](http://www.armacell.com.vn) • [info.vietnam@armacell.com](mailto:info.vietnam@armacell.com)  
**Armacell Asia Ltd. (Indonesia Representative Office)**  
Menara Karya, 28th Floor Jl. H.R. Rasuna Said Block X-5 Kav. • 12950 1-2 Jakarta  
• Indonesia  
Phone +62 21 5789 5548 • Fax +62 21 5789 5888

Phone +62 21 5789 5588 • Fax +62 21 5789 5888  
www.armacell.co.id • info.indonesia@armacell.com

**armacell Asia Ltd. (Philippines Representative Office)**  
5/f Builder's Center 170 Salcedo St. Legaspi Village • 1229 Makati City • Philippines  
Phone +63 2 902 0956 • Fax +63 2 902 0949  
www.armacell.com • info.philippines@armacell.com

## **Import and Distribution in Vietnam**

KIM DIEN REFRIGERATION CO., LTD

Add: 2nd Floor, No. 119 Nguyen Ngoc Nai Str, Thanh Xuan Dist, Hanoi

Tel: 84 4 3221 6236 Fax: 84 4 3576 5728

[Http://www.kimdienvn.com](http://www.kimdienvn.com)

E-mail: sales@kimdienvn.com